The listing of claims will replace all prior versions, and listings, of claims in the

application:

**Listing of Claims:** 

Claim 1 (Currently amended): An industrial robot comprising a first member and a

second member which rotate relatively at a joint portion thereof;

the first member including:

a first mount portion where a first positioning member is embedded and

a first guide portion along which the first positioning member slides in such a

manner as to produce protrude; and

the second member including:

an abutment portion which is brought into abutment with the first positioning

member when the first and second members are made to rotate relatively;

wherein the first positioning member and the guide member adopt a socket and spigot

construction which is free from mechanical loosening, and

wherein the first positioning member is held at a position where the first positioning

member does not protrude from the first member when performing a normal operation,

whereas only when performing an origin adjustment, the first positioning member is made to

<u>protrude</u>.

Claim 2 (withdrawn): An industrial robot comprising a first member and a second

member which rotate relatively at a joint portion thereof;

the first member including:

a first mount portion where a first positioning member is embedded and

Page 3 of 10

a first guide portion along which the first positioning member slides in such a

manner as to protrude; and

the second member including:

a second mount portion where a second positioning member is embedded and

a second guide portion along which the second positioning member slides in

such a manner as to protrude,

whereby the first and second positioning members are brought into abutment with each other

when the first member and the second member are made to rotate relatively.

Claim 3 (Currently amended): An industrial robot as set forth in Claim [[1 or]] 2,

wherein the positioning member is held at a position where the positioning member does not

protrude from the first member when performing a normal operation, whereas only when

performing an origin adjustment, the positioning member is made to protrude.

Claim 4 (Currently amended): An industrial robot as set forth in Claim 1 or 3,

wherein the first positioning member is brought into abutment as a mechanical origin position

of the industrial robot.

Claims 5-6 (canceled)

Claim 7 (Withdrawn): An industrial robot as set forth in Claim 1, wherein the

abutment portion of the second member includes:

a second mount portion where a second positioning member is embedded; and

a second guide portion along which the second positioning member slides in

Page 4 of 10

Appl. No. 10/536,594

Response Dated February 6, 2009

Reply to Office action of November 6, 2008

such a manner as to protrude,

wherein the second positioning member is brought into abutment with the first

positioning member when the first and second members are made to rotate relatively.

Claim 8 (new): An industrial robot as set forth in Claim 1, wherein the first

positioning member is provided without any actuating device, such that the first positioning

member must be manually slid in said manner so as to protrude.

Page 5 of 10